

Long-wave instability in shear flow

Liang Sun*

1. School of Earth and Space Sciences University of Science and Technology of China, Hefei, 230026, P.R.China.

2. LASG, Institute of Atmospheric Physics, Chinese Academy of Sciences, Beijing 100029, China

(Dated: January 10, 2010)

We prove here that the shortwaves in shear flows are always stable, whereas the shear flow instability is due to long-wave instability. For the unstable flows, an estimation of growth rate is obtained as $\omega_i \leq (p-1)\sqrt{\mu_1}|U_{\max} - U_{\min}|$, which is much better than the previous one obtained by Høiland and Howard. Comparing this with shortwave instability in Kelvin-Helmholtz (K-H) instability, it implies that the shear flow itself can damp the shortwaves without viscous effect. Further investigation shows that K-H instability is in essence of long-wave instability in shear flow. These results can be applied to verify numerical calculations.

PACS numbers: 47.15.Fe, 47.20.Cq, 47.20.-k, 47.32.Cc

Shear instability, caused by the velocity shear, is one of most important instabilities in the flows. Although the mechanism of shear instability is not full revealed yet, it is applied to explain the instability of mixing layer, jets in pipe, wakes behind cylinder, etc. Some simple models were employed to study the shear instability, including Kelvin-Helmholtz (K-H) model, piecewise linear velocity profile [1] and continued velocity profiles [2], etc. To reveal the mechanism of shear instability, the stability of perturbation waves should be understood. In K-H model, the growth rate of the disturbance wave is proportion to the product of wavenumber and velocity shear, thus the shortwaves are more unstable than longwaves in K-H model. However, Rayleigh [1] found that the piecewise linear profile is linearly unstable only in a finite range of wavenumbers $0 \leq k < k_c$, which means the shortwaves are stable in this case [1, 3–6]. A contradiction [4, 5] emerges as shortwave and longwave dominate the shear instability in K-H model and piecewise linear profiles, respectively. This was explained either as viscous effect must be considered for shortwave [5] or as longwaves do not “feel” the finite thickness of the layer [4, 5].

To dispel the contradiction, we should find out which dominates the shear instability, shortwave or longwave? It is from the numerical simulation (see [4, 5, 7] and references therein) and some theoretical analysis (e.g. Tollmien [8] and Lin [9]) that longwave might be more unstable than shortwave. They also proved the long-wave instability subject to the velocity profile U is either symmetric or monotone. We will investigate this problem following the way by Sun [10].

Moreover, a prior estimation of growth rate, which may be obtained from the investigation, is useful for unstable flows. For example, Howard’s semicircle theorem [11] has been used to validate the numerical calculations [7]. Another useful result was found by Høiland [12] and Howard [11] that the growth rate ω_i must less equate to half of the maxim of vorticity, i.e., $\omega_i \leq |U'|_{\max}/2$. But this

estimation is too cursory to be used in applications. For example, U' is always great than zero even the velocity profile has no inflection point. So this estimation is trivial for these cases. Here we will show a refinement estimation of growth rate, which can be applied to general velocity profiles in parallel flows.

The motivation of this short letter is to investigate these problems within the context of inviscid parallel flow. The aim here is to find out some general characters for unstable waves.

To this purpose, long-wave instability in shear flows is investigated via Rayleigh’s equation [2–5]. For a parallel flow with mean velocity $U(y)$, where y is the cross-stream coordinate. The streamfunction of the disturbance expands as series of waves (normal modes) with real wavenumber k and complex frequency $\omega = \omega_r + i\omega_i$, where ω_i relates to the grow rate of the waves. The flow is unstable if and only if $\omega_i > 0$. We study the stability of the disturbances by investigating the growth rate of the waves, this method is known as normal mode method. The amplitude of waves, namely ϕ , holds

$$(\phi'' - k^2\phi) - \frac{U''}{U-c}\phi = 0, \quad (1)$$

where $c = \omega/k = c_r + ic_i$ is the complex phase speed. The real part of complex phase speed $c_r = \omega_r/k$ is the wave phase speed. This equation is to be solved subject to homogeneous boundary conditions

$$\phi = 0 \text{ at } y = a, b. \quad (2)$$

From Rayleigh’s equation, we get the following equations:

$$\int_a^b [(\|\phi'\|^2 + k^2\|\phi\|^2) + \frac{U''(U-c_r)}{\|U-c\|^2}\|\phi\|^2] dy = 0, \quad (3)$$

and

$$c_i \int_a^b \frac{U''}{\|U-c\|^2} \|\phi\|^2 dy = 0. \quad (4)$$

Rayleigh used only Eq.(4) to prove his theorem, i.e., a necessary condition for instability is $U''(y_s) = 0$, where

*Electronic address: sunl@ustc.edu.cn; sunl@ustc.edu

y_s is the inflection point and $U_s = U(y_s)$ is the velocity at y_s . Before the further discussion, we need estimate the rate of $\int_a^b \|\phi'\|^2 dy$ to $\int_a^b \|\phi\|^2 dy$, as Sun did [10]. This is known as Poincaré's problem:

$$\int_a^b \|\phi'\|^2 dy = \mu \int_a^b \|\phi\|^2 dy, \quad (5)$$

where the eigenvalue μ is positive definition for $\phi \neq 0$. The smallest eigenvalue value, namely μ_1 , can be estimated as $\mu_1 > (\frac{\pi}{b-a})^2$. And an auxiliary function $f(y) = \frac{U''}{U-U_s}$ is also introduced, where $f(y)$ is finite at inflection point.

With the preparation above, we have such consequence. If $-f(y) < Q < \infty$, where Q is a positive constant, then the disturbances with shortwaves $k > k_c$ are always stable, where k_c is a critical wavenumber subject to $k_c^2 = Q - \mu_1$. We will prove the consequence by two steps. At first, we prove proposition 1: if $c_r = U_s$, the disturbances with shortwaves $k > k_c$ are always stable.

Proof: Since $U'' = f(y)(U - U_s)$, $c_r = U_s$ and $f(y) < 0$, this yields to

$$\frac{U''(U - U_s)}{\|U - c\|^2} = \frac{f(y)(U - U_s)^2}{(U - c_r)^2 + c_i^2} > f(y) > -Q, \quad (6)$$

and

$$\begin{aligned} \int_a^b [(\|\phi'\|^2 + k^2\|\phi\|^2) + \frac{U''(U - U_s)}{\|U - c\|^2} \|\phi\|^2] dy &\geq \\ \int_a^b [(\mu_1 + k_c^2 + \frac{U''(U - U_s)}{\|U - c\|^2}) \|\phi\|^2] dy &> 0. \end{aligned} \quad (7)$$

This contradicts Eq.(3). So proposition 1 is proved.

Then, we prove proposition 2: if $c_r \neq U_s$, there must be $c_i^2 = 0$ with $k > k_c$.

Proof: Otherwise if $c_i^2 \neq 0$, so according to Eq.(3) and Eq.(4), for any arbitrary real number U_t which does not depend on y , it holds

$$\int_a^b [(\|\phi'\|^2 + k^2\|\phi\|^2) + \frac{U''(U - U_t)}{\|U - c\|^2} \|\phi\|^2] dy = 0. \quad (8)$$

But the above Eq.(8) can not be hold for some special U_t . For example, let $U_t = 2c_r - U_s$, then there is $(U - U_s)(U - U_t) < \|U - c\|^2$, and

$$\frac{U''(U - U_t)}{\|U - c\|^2} = f(y) \frac{(U - U_s)(U - U_t)}{\|U - c\|^2} > -Q. \quad (9)$$

For $k > k_c$, this yields to

$$\int_a^b \{ \|\phi'\|^2 + [k^2 + \frac{U''(U - U_t)}{\|U - c\|^2}] \|\phi\|^2 \} dy > 0, \quad (10)$$

which also contradicts Eq.(8). So proposition 2 is also proved. These two propositions are natural generalization of stable criterion proved by Sun [13].

From the above two propositions, we can draw a conclusion that the disturbances with shortwaves $k > k_c$ are

always stable. This means that the shear instability in flows must be long-wave instability. Furthermore, the short-wave stability means that without any viscous effect, the shortwaves can also be damped by shear flow. This mechanism is unlike the viscous mechanism that the viscosity has a damping effect on especially the shortwaves. It implies that the shear flow itself can damp the shortwaves. This is very general and important conclusion, which explains why the instabilities found in shear flows are mostly long-wave instabilities.

This result is also very important for numerical calculation, which means shortwaves can be truncated in the calculations without changing the stability of shear flow. So the growth rates of longwaves have enough information for judging the stability of shear flow. On the other hand, the truncation of longwaves would probably change the instability of the shear flow. So the streamwise length scale must be longer enough to have longwaves for the numerical simulations in shear flows, such as plane parallel flow and pipe flow. Otherwise the instability of shear flow would be damped without long-wave perturbations.

Then the growth rate of unstable waves can be estimated here by following the former investigation. Similar to the assumption above, $-f(y) < Q = p^2 \mu_1 < \infty$, where $1 < p < 2$, we will show that the growth rate is subject to $\omega_i \leq (p-1)\sqrt{\mu_1}|U_{\max} - U_{\min}|$.

Proof: It is from Eq.(3) that gives

$$\int_a^b k^2 \|\phi\|^2 dy = \int_a^b -[\|\phi'\|^2 + \frac{U''(U - c_r)}{\|U - c\|^2} \|\phi\|^2] dy. \quad (11)$$

Substituting Eq.(5) to Eq.(11) and recalling that $\mu_1 < \mu$, this yields

$$\int_a^b k^2 \|\phi\|^2 dy \leq \int_a^b -[\frac{U''(U - c_r)}{\|U - c\|^2} + \mu_1] \|\phi\|^2 dy. \quad (12)$$

Multiplying above inequality (12) by c_i^2 , we get

$$\omega_i^2 \int_a^b \|\phi\|^2 dy \leq \int_a^b h(y) \|\phi\|^2 dy, \quad (13)$$

where

$$h(y) = -[\frac{U''(U - c_r)}{\|U - c\|^2} + \mu_1] c_i^2. \quad (14)$$

Suppose the maxim of $h(y)$ is P^2 , then the growth rate is subject to

$$\omega_i^2 \leq P^2. \quad (15)$$

This follows

$$h(y) \leq -[\frac{U''(U - c_r)}{(U - c_r)^2 + c_i^2} + \mu_1] c_i^2. \quad (16)$$

Substitution of $f(y)$ into Eq.(16), gives

$$h(y) \leq \mu_1 [\frac{(p^2 - 1)(U - c_r)^2 - c_i^2}{(U - c_r)^2 + c_i^2}] c_i^2. \quad (17)$$

When

$$c_i^2 = (p-1)(U - c_r)^2, \quad (18)$$

the right hand of Eq.(17) get its largest value

$$P^2 = (p-1)^2 \mu_1 (U - c_r)^2. \quad (19)$$

Then the growth rate must be subject to

$$\omega_i \leq (p-1)\sqrt{\mu_1}|U_{\max} - U_{\min}|, \quad (20)$$

where $U_{\min}$ and $U_{\max}$ are minimum and maximum of $U(y)$, respectively. And the wavenumber $k_{\max}$ corresponding to the largest growth rate is

$$k_{\max} = \sqrt{(p-1)\mu_1}. \quad (21)$$

So the result is proved. One should note that the fast growth rate ω_i is only an approximation, but not a precision one, so as to wavenumber $k_{\max}$.

Comparing with the previous one by Høiland and Howard, the above estimation includes not only a more precision estimation about the the growth rate of unstable waves but also the regime of unstable wavenumbers. This would be much helpful for validation in numerical calculations.

As well known, the instability due to velocity shear is always associated to Kelvin-Helmholtz instability (K-H instability), in which the disturbances of all wavelengths are amplified. According to K-H instability, the shorter the wavelength is, the faster the perturbation wave amplifies. As the above investigation points out that the shortwaves are always more unstable than longwaves in this case, the contradiction at the beginning can be dispelled.

An physical explanation [4, 5] to the contradiction is that the K-H instability model has no intrinsic length scale, while Rayleigh's model has width of shear layer

as length scale of waves. This can be noted from that Rayleigh's case reduces to the Kelvin-Helmholtz vortex sheet model in the long-wave limit $k \ll 1$ [4, 5], which is dramatically explained as longwave do not "feel" the finite thickness of the shear layer [4]. Here we will show that this explanation can be extend to shear flows. It is from Eq.(21) that the fastest growing wavenumber $k_{\max}$ is proportion to $\sqrt{\mu_1}$, then the corresponding wave length $\lambda_{\max}$ is approximately $2(b-a)/\sqrt{p-1}$. So the thinner the shear layer is, the larger the fastest growing wavenumber is. It can be seen that the asymptotic case of infinite small shear layer leads to K-H instability. This is another evidence that K-H instability is in essence of long-wave instability. In this case, the K-H instability is an approximation of shear instability when the wave length of perturbation is much longer than the width of shear layer.

In summary, two general properties of shear instability are obtained in the investigations. Firstly, the short-waves are always stable in the continued profile flows and the shear instability is due to long-wave instability. This implies that the shear flow itself can damp the short-waves and that K-H instability is in essence of long-wave instability in shear flow. The result can be used to understand the phenomena in hydrodynamics instabilities. Secondly, the growth rate of unstable flow can be estimated as $\omega_i \leq (p-1)\sqrt{\mu_1}(U_{\max} - U_{\min})$. This estimation extend the previous result obtained by Høiland and Howard. Both results are important in numerical applications. The first one provides the estimation of unstable wavenumbers, and the second one provides the estimation of growth rate of unstable waves. These results may be useful on both numerical calculation and stability analysis.

This work is supported by the National Basic Research Program of China (No. 2007CB816004), the National Foundation of Natural Science (No. 40705027).

-
- [1] L. Rayleigh, *The Theory of Sound* (Macmillan, London, 1894).
 - [2] L. Rayleigh, Proc. London Math. Soc. **11**, 57 (1880).
 - [3] S. Chandrasekhar, *Hydrodynamic and Hydromagnetic Stability* (Dover Publications, Inc., New York, U.S.A., 1961).
 - [4] P. Huerre and M. Rossi, in *Hydrodynamics and nonlinear instabilities*, edited by C. Godrèche and P. Manneville (Cambridge University Press, Cambridge, 1998).
 - [5] W. O. Criminale, T. L. Jackson, and R. D. Joslin, *Theory and computation of hydrodynamic stability* (Cambridge University Press, Cambridge, U.K., 2003).
 - [6] P. G. Drazin and W. H. Reid, *Hydrodynamic Stability* (Cambridge University Press, 2004).
 - [7] P. J. Schmid and D. S. Henningson, *Stability and Transition in Shear Flows* (Springer-Verlag, 2000).
 - [8] W. Tollmien, Tech. Rep. NACA TM-792, NACA (1936).
 - [9] C. C. Lin, *The Theory of Hydrodynamic Stability* (Cambridge University Press, London, UK, 1955).
 - [10] L. Sun, Eur. J. Phys. **28**, 889 (2007).
 - [11] L. N. Howard, J. Fluid Mech. **10**, 509 (1961).
 - [12] E. Høiland, Geofysiske Publikasjoner **18**, 1 (1953).
 - [13] L. Sun, Chin. Phys. Lett. **25**, 1343 (2008).